



Checklist turnstile for creating a quotation

Company Name Date
 Inquiry-No. Project Amount

Please send to: info@axel-tiede.de Internal use: offer no. AG20 ____ - ____
 Fax: +49 2331 9461 48

Type Mechanic Electro-mechanic Electric
 Electro-mechanic with side passage Electric with side passage

Material Hot dip galvanized Stainless steel powder coated

Color Hot dipped galvanized/RAL 7040 for top box RAL7030 (Standard) Special-color RAL
 RAL7016 (Standard)

Top box Cover bolted Cover hinged Tube (for mechanic)
 Heating system (250W)

Roof none (only top box) Protection from metal sheet with climbing protection (Width 300mm) Large (2,4m x 2,4m) metal hinged with gas damper
 Drainage Large (2,4m x 2,4m) transparent hinged with gas damper

Guidance Guidance box for control units at entrance and exit side (standard with stainless steel) Guidance frame (standard with galvanized)

Passing width mm 650mm (Standard) up to 1.500mm possible

Position spindle arms 120° (Standard) 90°

Entrance side Right (Standard) Left

Power failure Free towards exit (standard) Free towards entrance Free in both directions

Mounting Foundation (NN - 20cm) and pavement Mounting onto floor Mobile with ground plate out of steel grating

Transportation Transport- and assembly frame, need only for fork lift (Standard) In single pieces No forklift on site
 Ex works DAP city:

Accessories LED lights Control box large (H256xB206xT103 mm) Control box small (H156xB106xT70mm)
 Damping switch Fence connector (single) Fence connector (double)
 Emergency power supply Cut out(s) for units supplied, please submit details Assembly units supplied
 Pulling wir for cable

Other Complete with access control system, short description
 Traffic light
 Stainless steel spindle polished
 Mounting set
 Assembly and start up
 Maintenance contract
 Other / remarks



In case of questions please contact us under (+49 2331 9461 25, info@axel-tiede.de).